

**Art. J272BU+D373AU**  
**3/4" Thermostatic mixer with 3-way diverter**

- For horizontal installation
- 3/4" NPT inlets and 1/2" outlets
- With shut-off valve
- Rectangular backplate
- Handle included
- Sound insulation foam back
- 8.7 GPM @ 60 PSI ( primary outlet )
- 7.4 GPM @ 60 PSI ( secondary outlet )
- 7.4 GPM @ 60 PSI (third outlet )

**External piece**  
**Finishes:**

- ☐
**Matte Gun Metal PVD**
67 P6 J272BU
- ☐
**Matte British Gold PVD**
67 P5 J272BU
- ☐
**Deep Black PVD**
67 S1 J272BU

**Built-in piece**  
**Finishes:**

- ☐
19 00 D373AU

**Project:**

**Room:**

**Date:**

**Comments:**

1st function	
Pressure (bar)	flow rate (l/min)
0,5	8,86
1	17,57
2	21,63
3	25,02
4	27,95

2nd function	
Pressure (bar)	flow rate (l/min)
0,5	7,91
1	15,47
2	19,01
3	21,98
4	24,62

3rd function	
Pressure (bar)	flow rate (l/min)
0,5	7,6
1	15,43
2	18,87
3	21,91
4	24,58

