



ART. G876BU+D377AU

3 way diverter with integrated volume control

- For remote installation
- 1/2" NPT inlets and outlets
- Flow rate: 8.7 gpm @ 60 psi (primary outlet)
- Flow rate: 7.4 gpm @ 60 psi (secondary outlet)
- Flow rate: 7.4 gpm @ 60 psi (third outlet)

To be used with thermostatic mixer G800BU+D400AU

Date _____

Project/Comments: _____

Trim

- | | |
|--|--------------|
| <input type="checkbox"/> Chrome | 31 02 G876BU |
| <input type="checkbox"/> Polished Nickel PVD | 31 95 G876BU |
| <input type="checkbox"/> Matte Gun Metal PVD | 31 P5 G876BU |
| <input type="checkbox"/> Matte British Gold PVD | 31 P6 G876BU |
| <input type="checkbox"/> Matte Copper PVD | 31 P9 G876BU |
| <input type="checkbox"/> Deep Black PVD | 31 S1 G876BU |
| <input type="checkbox"/> Pure Brass PVD | 31 Q7 G876BU |
| <input type="checkbox"/> Raw Metal PVD | 31 Q8 G876BU |
|
 | |
| <input type="checkbox"/> Brushed Stainless steel | 31 93 G876BU |

Rough

- | | |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D377AU |
|--------------------------|--------------|

TOTAL PRICE

- | | |
|--|--------------|
| <input type="checkbox"/> Chrome | 31 02 G876BU |
| <input type="checkbox"/> Polished Nickel PVD | 31 95 G876BU |
| <input type="checkbox"/> Matte Gun Metal PVD | 31 P5 G876BU |
| <input type="checkbox"/> Matte British Gold PVD | 31 P6 G876BU |
| <input type="checkbox"/> Matte Copper PVD | 31 P9 G876BU |
| <input type="checkbox"/> Deep Black PVD | 31 S1 G876BU |
| <input type="checkbox"/> Pure Brass PVD | 31 Q7 G876BU |
| <input type="checkbox"/> Raw Metal PVD | 31 Q8 G876BU |
|
 | |
| <input type="checkbox"/> Brushed Stainless steel | 31 93 G876BU |

ART. G876BU+D377AU

3 way diverter with integrated volume control

