



ART. 0676BU+D276AU

2-Way diverter with integrated volume control

- For remote installation
- 1/2" NPT inlets and outlets
- With shut off valve
- Flow rate: 8.9 gpm @ 60 psi (primary outlet)
- Flow rate: 7.6 gpm @ 60 psi (secondary outlet)

To be used with thermostatic valve (#0600BU+#4700AU)

Any RAL color available upon request

Date _____

Project/Comments: _____

Trim

- | | |
|--------------------------------------|--------------|
| <input type="checkbox"/> Matte Black | 60 13 0676BU |
| <input type="checkbox"/> Matte White | 60 29 0676BU |
| <input type="checkbox"/> Red | 60 06 0676BU |
| <input type="checkbox"/> RAL Color * | 60 _ 0676BU |

Rough

- | | |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D276AU |
|--------------------------|--------------|

TOTAL PRICE

- | | |
|--------------------------------------|--------------|
| <input type="checkbox"/> Matte Black | 60 13 0676BU |
| <input type="checkbox"/> Matte White | 60 29 0676BU |
| <input type="checkbox"/> Red | 60 06 0676BU |
| <input type="checkbox"/> RAL Color * | 60 _ 0676BU |

ART. 0676BU+D276AU

2-Way diverter with integrated volume control

