



ART. G572BU+D373AU

3/4" Thermostatic mixer with 3-way diverter

- Temperature control with safety override button at 100° F
- 3/4" NPT inlets, 1/2" outlets on rough
- Flow rate: 8.7 gpm @ 60 psi (primary outlet)
- Flow rate: 7.4 gpm @ 60 psi (secondary outlet)
- Flow rate: 7.4 gpm @ 60 psi (third outlet)
- Anti-scald mechanism
- Watertight casing for added safety
- Accessible shut-off valves and filters
- For horizontal installation

Date _____

Project/Comments: _____

Trim

- | | |
|---|--------------|
| <input type="checkbox"/> Chrome | 87 02 G572BU |
| <input type="checkbox"/> Polished Nickel PVD | 87 95 G572BU |
| <input type="checkbox"/> Matte Gun Metal PVD | 87 P5 G572BU |
| <input type="checkbox"/> Matte British Gold PVD | 87 P6 G572BU |
| <input type="checkbox"/> Matte Copper PVD | 87 P9 G572BU |
| <input type="checkbox"/> Gold Plus | 87 01 G572BU |

Rough

- | | |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D373AU |
|--------------------------|--------------|

TOTAL PRICE

- | | |
|---|--------------|
| <input type="checkbox"/> Chrome | 87 02 G572BU |
| <input type="checkbox"/> Polished Nickel PVD | 87 95 G572BU |
| <input type="checkbox"/> Matte Gun Metal PVD | 87 P5 G572BU |
| <input type="checkbox"/> Matte British Gold PVD | 87 P6 G572BU |
| <input type="checkbox"/> Matte Copper PVD | 87 P9 G572BU |
| <input type="checkbox"/> Gold Plus | 87 01 G572BU |

ART. G572BU+D373AU

3/4" Thermostatic mixer with 3-way diverter

