

**ART. G572BU+D372AU****3/4" Thermostatic mixer with 2-way diverter**

- Temperature control with safety override button at 100° F
- 3/4" NPT inlets, 1/2" outlets on rough
- Flow rate: 8.9 gpm @ 60 psi (primary outlet)
- Flow rate: 7.6 gpm @ 60 psi (secondary outlet)
- Anti-scald mechanism
- Watertight casing for added safety
- Accessible shut-off valves and filters
- For horizontal installation

Date**Project/Comments:**

Trim

<input type="checkbox"/> Chrome	87 02 G572BU
<input type="checkbox"/> Polished Nickel PVD	87 95 G572BU
<input type="checkbox"/> Matte Gun Metal PVD	87 P5 G572BU
<input type="checkbox"/> Matte British Gold PVD	87 P6 G572BU
<input type="checkbox"/> Matte Copper PVD	87 P9 G572BU
<input type="checkbox"/> Gold Plus	87 01 G572BU

TOTAL PRICE

<input type="checkbox"/> Chrome	87 02 G572BU
<input type="checkbox"/> Polished Nickel PVD	87 95 G572BU
<input type="checkbox"/> Matte Gun Metal PVD	87 P5 G572BU
<input type="checkbox"/> Matte British Gold PVD	87 P6 G572BU
<input type="checkbox"/> Matte Copper PVD	87 P9 G572BU
<input type="checkbox"/> Gold Plus	87 01 G572BU

Rough

<input type="checkbox"/>	19 00 D372AU
--------------------------	--------------

ART. G572BU+D372AU

3/4" Thermostatic mixer with 2-way diverter

