



### ART. P872BU+D373AU

#### 3/4" Thermostatic mixer with 3-way diverter

- Temperature control with safety override button at 100° F
- 3/4" NPT inlets, 1/2" outlets on rough
- Flow rate: 8.7 gpm @ 60 psi (primary outlet)
- Flow rate: 7.4 gpm @ 60 psi (secondary outlet)
- Flow rate: 7.4 gpm @ 60 psi (third outlet)
- Anti-scald mechanism
- Watertight casing for added safety
- Accessible shut-off valves and filters
- For horizontal installation

Date \_\_\_\_\_

Project/Comments: \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

#### Trim

- Polished Nickel PVD            49 95 P872BU
- Matte Gun Metal PVD            49 P5 P872BU
  
- Brushed Stainless steel            49 93 P872BU

#### Rough

- 19 00 D373AU

#### TOTAL PRICE

- Polished Nickel PVD            49 95 P872BU
- Matte Gun Metal PVD            49 P5 P872BU
  
- Brushed Stainless steel            49 93 P872BU

# O-XY

## ART. P872BU+D373AU

3/4" Thermostatic mixer with 3-way diverter

