



**ART. G576BU+D377AU**

**3-Way diverter with integrated volume control**

- For remote installation
- 1/2" NPT inlets and outlets
- Accessible shut-off valves and filters
- Flow rate: 8.7 gpm @ 60 psi (primary outlet)
- Flow rate: 7.4 gpm @ 60 psi (secondary outlet)
- Flow rate: 7.4 gpm @ 60 psi (third outlet)

To be used with thermostatic mixer G500BU+D400AU

**Date**

---

**Project/Comments:**

---



---



---



---



---



---



---

**Trim**

- |   |              |
|---|--------------|
| <input type="checkbox"/> Chrome                 | 87 02 G576BU |
| <input type="checkbox"/> Matte Black            | 87 13 G576BU |
| <input type="checkbox"/> Matte Gun Metal PVD    | 87 P5 G576BU |
| <input type="checkbox"/> Matte British Gold PVD | 87 P6 G576BU |
| <input type="checkbox"/> Matte Copper PVD       | 87 P9 G576BU |
| <input type="checkbox"/> Deep Black PVD         | 87 S1 G576BU |

**Rough**

- |                          |              |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D377AU |
|--------------------------|--------------|

**TOTAL PRICE**

- |   |              |
|---|--------------|
| <input type="checkbox"/> Chrome                 | 87 02 G576BU |
| <input type="checkbox"/> Matte Black            | 87 13 G576BU |
| <input type="checkbox"/> Matte Gun Metal PVD    | 87 P5 G576BU |
| <input type="checkbox"/> Matte British Gold PVD | 87 P6 G576BU |
| <input type="checkbox"/> Matte Copper PVD       | 87 P9 G576BU |
| <input type="checkbox"/> Deep Black PVD         | 87 S1 G576BU |

# MYO



## ART. G576BU+D377AU

3-Way diverter with integrated volume control

