



ART. G576BU+D376AU

2-Way diverter with integrated volume control

- For remote installation
- 1/2" NPT inlets and outlets
- Accessible shut-off valves and filters
- Flow rate: 8.9 gpm @ 60 psi (primary outlet)
- Flow rate: 7.6 gpm @ 60 psi (secondary outlet)

To be used with thermostatic mixer G500BU+D400AU

Date

Project/Comments:

Trim

- | | |
|---|--------------|
| ☐ Chrome | 87 02 G576BU |
| ☐ Matte Black | 87 13 G576BU |
| ☐ Matte Gun Metal PVD | 87 P5 G576BU |
| ☐ Matte British Gold PVD | 87 P6 G576BU |
| ☐ Matte Copper PVD | 87 P9 G576BU |
| ☐ Deep Black PVD | 87 S1 G576BU |

Rough

- | | |
|--------------------------|--------------|
| ☐ | 19 00 D376AU |
|--------------------------|--------------|

TOTAL PRICE

- | | |
|---|--------------|
| ☐ Chrome | 87 02 G576BU |
| ☐ Matte Black | 87 13 G576BU |
| ☐ Matte Gun Metal PVD | 87 P5 G576BU |
| ☐ Matte British Gold PVD | 87 P6 G576BU |
| ☐ Matte Copper PVD | 87 P9 G576BU |
| ☐ Deep Black PVD | 87 S1 G576BU |

MYO



ART. G576BU+D376AU

2-Way diverter with integrated volume control

