



ART. N376SBU+N376AU

2-Way diverter with integrated volume control

- For remote installation
- 1/2" NPT inlets and outlets
- Accessible shut-off valves and filters
- Without handle
- Flow rate: 8.9 gpm @ 60 psi (primary outlet)
- Flow rate: 7.6 gpm @ 60 psi (secondary outlet)

To be used with thermostatic mixer G500BU+D400AU

Handle to be ordered separately, please refer to Handles section

Date

Project/Comments:

Trim

- | | |
|---|---------------|
| <input type="checkbox"/> Chrome | 29 02 N376SBU |
| <input type="checkbox"/> Polished Nickel PVD | 29 95 N376SBU |
| <input type="checkbox"/> Matte Gun Metal PVD | 29 P5 N376SBU |
| <input type="checkbox"/> Matte British Gold PVD | 29 P6 N376SBU |
| <input type="checkbox"/> Matte Copper PVD | 29 P9 N376SBU |
| <input type="checkbox"/> Pure Brass PVD | 29 Q7 N376SBU |
| <input type="checkbox"/> Raw Metal PVD | 29 Q8 N376SBU |
| <input type="checkbox"/> Gold Plus | 29 01 N376SBU |

Rough

- | | |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 N376AU |
|--------------------------|--------------|

TOTAL PRICE

- | | |
|---|---------------|
| <input type="checkbox"/> Chrome | 29 02 N376SBU |
| <input type="checkbox"/> Polished Nickel PVD | 29 95 N376SBU |
| <input type="checkbox"/> Matte Gun Metal PVD | 29 P5 N376SBU |
| <input type="checkbox"/> Matte British Gold PVD | 29 P6 N376SBU |
| <input type="checkbox"/> Matte Copper PVD | 29 P9 N376SBU |
| <input type="checkbox"/> Pure Brass PVD | 29 Q7 N376SBU |
| <input type="checkbox"/> Raw Metal PVD | 29 Q8 N376SBU |
| <input type="checkbox"/> Gold Plus | 29 01 N376SBU |

ART. N376SBU+N376AU

2-Way diverter with integrated volume control

