



ART. F472BU+D331AU

3/4" Thermostatic mixer with integrated volume control

- Temperature control with safety override button at 100° F
- 3/4" NPT inlets, 1/2" outlet on rough
- Flow rate: 15.3 gpm @ 60 psi
- Anti-scald mechanism
- Watertight casing for added safety
- Accessible shut-off valves and filters
- For horizontal installation

Date _____

Project/Comments: _____

Trim

- | | |
|--------------------------------------------------|--------------|
| <input type="checkbox"/> Chrome | 34 02 F472BU |
| <input type="checkbox"/> Matte Black | 34 13 F472BU |
| <input type="checkbox"/> Matte Gun Metal PVD | 34 P5 F472BU |
| <input type="checkbox"/> Matte British Gold PVD | 34 P6 F472BU |
| <input type="checkbox"/> Matte Copper PVD | 34 P9 F472BU |
| <input type="checkbox"/> Deep Black PVD | 34 S1 F472BU |
|
 | |
| <input type="checkbox"/> Brushed Stainless steel | 34 93 F472BU |

Rough

- | | |
|--------------------------|--------------|
| <input type="checkbox"/> | 19 00 D331AU |
|--------------------------|--------------|

TOTAL PRICE

- | | |
|--------------------------------------------------|--------------|
| <input type="checkbox"/> Chrome | 34 02 F472BU |
| <input type="checkbox"/> Matte Black | 34 13 F472BU |
| <input type="checkbox"/> Matte Gun Metal PVD | 34 P5 F472BU |
| <input type="checkbox"/> Matte British Gold PVD | 34 P6 F472BU |
| <input type="checkbox"/> Matte Copper PVD | 34 P9 F472BU |
| <input type="checkbox"/> Deep Black PVD | 34 S1 F472BU |
|
 | |
| <input type="checkbox"/> Brushed Stainless steel | 34 93 F472BU |

ART. F472BU+D331AU

3/4" Thermostatic mixer with integrated volume control

