



ART. K002

Rain showerhead

- frame 35x35 cm
- showerhead 30x30 cm
- built-in part included
- check valve
- For ceiling installation: built-in piece, partially built-in piece, external piece
- systemOCS, Optimal Closing System

- flow restrictor 12 l/min at 3 bar

Water functions:

- 1st function: 125 anti - limestone nozzles

NOTE: conditions necessary for the correct functioning: Min.

Flow Rate: 9 l/min

NOTE: To choose the mixer please refer to the pages with shower compositions for each collection

Finish:

- | | |
|---|------------|
| <input type="checkbox"/> Brilliant Stainless Steel | 79 38 K002 |
| <input type="checkbox"/> Matt Black | 79 13 K002 |
| <input type="checkbox"/> Matt White | 79 29 K002 |
| <input type="checkbox"/> Polished Nickel PVD | 79 95 K002 |
| <input type="checkbox"/> Matt Gun Metal PVD | 79 P5 K002 |
| <input type="checkbox"/> Matt British Gold PVD | 79 P6 K002 |
| <input type="checkbox"/> Matt Copper PVD | 79 P9 K002 |
| <input type="checkbox"/> Deep Black PVD | 79 S1 K002 |
| <input type="checkbox"/> Mokka PVD | 79 S5 K002 |
| <input type="checkbox"/> Brushed Steel Look PVD | 79 92 K002 |
| <input type="checkbox"/> Golden Look PVD | 79 S9 K002 |
| <input type="checkbox"/> Pure Brass PVD | 79 Q7 K002 |
| <input type="checkbox"/> Raw Metal PVD | 79 Q8 K002 |
| <input type="checkbox"/> Brushed Stainless Steel | 79 93 K002 |

Date _____

Project/Comments: _____

• 1st function: 125 anti - limestone nozzles

Pressure(bar)	Flow rate (l/min)
0.5	6.16
1	10.98
2	12.22
3	11.69
4	11.71