



ART. K073

Rain showerhead

- Ø 30 cm
- check valve
- 1/2" inlet
- anti-lime scale system
- wall-mount
- systemOCS, Optimal Closing System

- flow restrictor 14 l/min at 3 bar

Water functions:

- 1st function: 240 anti - limestone nozzles

NOTE: conditions necessary for the correct functioning: Min.

Flow Rate: 12 l/min

NOTE: Shower arm to be separatly ordered

NOTE: To choose the mixer please refer to the pages with shower compositions for each collection

Finish:

- | | |
|---|------------|
| <input type="checkbox"/> Brilliant Stainless Steel | 79 38 K073 |
| <input type="checkbox"/> Matt Black | 79 13 K073 |
| <input type="checkbox"/> Matt White | 79 29 K073 |
| <input type="checkbox"/> Polished Nickel PVD | 79 95 K073 |
| <input type="checkbox"/> Matt Gun Metal PVD | 79 P5 K073 |
| <input type="checkbox"/> Matt British Gold PVD | 79 P6 K073 |
| <input type="checkbox"/> Matt Copper PVD | 79 P9 K073 |
| <input type="checkbox"/> Deep Black PVD | 79 S1 K073 |
| <input type="checkbox"/> Mokka PVD | 79 S5 K073 |
| <input type="checkbox"/> Brushed Steel Look PVD | 79 92 K073 |
| <input type="checkbox"/> Golden Look PVD | 79 S9 K073 |
| <input type="checkbox"/> Pure Brass PVD | 79 Q7 K073 |
| <input type="checkbox"/> Raw Metal PVD | 79 Q8 K073 |
| <input type="checkbox"/> Brushed Stainless Steel | 79 93 K073 |

Date _____

Project/Comments: _____

• 1st function: 240 anti - limestone nozzles

Pressure(bar)	Flow rate (l/min)
0.5	6.57
1	9.83
2	13.35
3	15.38
4	14.52