


UNDER- BODY COATING

Undervorgens belægning | Sassiikaitse | Revestimiento del chásis | Revêtement
de soubassement | Alvázzévdó bevonat | Rivestimento Sottoscocca | Automobilió paçios
apsaço | Šasijas aizsardzība | Coating voor de onderkant | Understell behandeling | Šrodek
do ochrony karoserii | Chassis chapeamento | Protecția caroseriei | Средство для защиты
шасси | Ochranný náter podvozku



Black | Musta | Svart | Černá | Schwarz | Sort | Must
Negro | Noir | Fekete | Nero | Juoda | Melns | Zwart
Sort | Czarny | Preto | Negru | Черный | Čierna

[illegible][illegible]

Danger | Vaara | Fara | Nebezpečí | Gefahr | Fare |
Ettevaatust | Peligro | Danger | Veszély | Pericolo |
Pavojinga | Draudi | Gevaar | Fare | Niebezpieczeństwo |
Perigo | Pericol | Опасность | Nebezpečnostvo

II B (e) VOC/LOÜ/ЛОВ-/ЛОJ max. 840g/l (2010). VOC 571 g/l

Manufacturer: Maston Oy • www.maston.fi • maston@maston.fi

Teollisuustie 10, FI-02880 Veikkola, FINLAND, Tel. +358 20 7188 580 • Fax +358 20 7188 599
Террловистие 10, 02880 Вейккола, Финляндия, Тел. +358 20 7188 580 • Факс +358 20 7188 599

ART. NR
4150110
10

