


SILVER
GREY

Silver Grey | Hopeanharmaa | Silvergrå | Сребърен сиво
Sølvgrå | Hõbehall | Ασμί γκρι | Sidabro pilkumo
Zilganpelēka | Sølvgrå | Серое серебро | Gümüş grisi



COVERAGE




HIGH FILLI POWER




QUICK DRYING



RUST STOP



MATERIAL



HARDNESS

Hardness | Kovuus | Hårdhet | Твърдост | Hårdhed | Kõvadus | Σκληρότητα
Tvirtumas | Cietība | Hardhet | Твердость | Sertlik

ZINC

Aluminium

Cold Galvanized Zinc | Vaalea Kylmägalvanointi Sinkki
Ljus zink för kallförzinkning | Студено цинкована
Koldgalvanisering zink | Hele tsink külmgalvaaniseks
Ψυχρό Γαλβάνισμα Ψευδαργύρου | Šviesasis cinkas šaltam galvanizavimui
Gaiši cinkots | Lys Zink Kaldgalvanisering
Светлый цинк для холодной гальваники | Soğuk Galvanize Cinko



SOFT


CLEAN UP



1



CLEAN

[illegible]

EN: INCLUDES: Acetone: Butyl Acetate: 2-butanone

Danger | Vaara | Fara | Опасно | Fare | Ettevaatust | Κίνδυνος
Pavojinga | Draudi | Fare | Опасность | Tehlike

II B (e) VOC/LOÜ/ΠΟΒ-/LOJ
max. 840g/l (2010). VOC 626.07/

400 ml netto / net / нетто. 3 520 MAL 3-1

Manufacturer: Maston Oy • www.maston.fi • maston@maston.fi
Teollisuustie 10, FI-02880 Veikkola, FINLAND, Tel. +358 20 7188 580 • Fax +358 20 7188 599
Тео́ллу́стие 10, 02880 Вейккола, Финляндия, Тел. +358 20 7188 580 • Факс +358 20 7188 599

ART. NR.
400172
21

