

Off-road lift table truck XOFFROAD





Why XOFFROAD?

Our XOFFROAD off-road push bar lift table truck not only enables easy loading and unloading in a normal environment such as warehouses or other indoor spaces, but also off-road as well as on construction sites and uneven gravel sites. With a load capacity of 200kg, machines, racks or storage areas can be filled without any problems due to the large ground clearance in outdoor areas.

- Problem-free use indoors and outdoors
- Optimal use for uneven surfaces due to the **large ground clearance**

- Quiet running and good off-road capability due to large-profile rubber rollers
- With a table size of 1000 x 500 mm also very suitable for **bulky goods**
- Allows pleasant, ergonomic work, due to the flexibly adjustable table height of 1010 mm
- Features a foldable push bar



Technical data

Off-road lift table truck XOFFROAD

DIMENSIONS

Max. platform height	1010 mm	
Min. platform height	330 mm	h13
Platform length	1000 mm	12
Platform width	500 mm	
Total maximum height	1010 mm	
Total height:	360 mm	
Width	620 mm	b1
Length	1180 mm	1
Height	1055 mm	
Wheel base	860 mm	

GENERAL INFORMATION

Load capacity	200 kg
Lift type	Manual hydraulic
Driving distance	Average distance
Colour	Ultramarine blue
Weight	73 kg
Type of brakes	Parking break
Type of drive	Manual





LIFT

1010 mm
10
70 mm
680 mm

TYRES

Material of tyres	Rubber
Width of casters	40 mm
Diameter of casters	200 mm
Width of swivel casters	40 mm
Diameter of casters	200 mm

We are improving our products continuously. It is therefore possible that technical data changes without prior notice. Details to our manufacturer warranty available under Declaration of warranty. The platform trolley complies with the EC Safety regulations.

Images

Off-road lift table truck XOFFROAD















Images Off-road lift table truck XOFFROAD









Why Pallit?

- Delivery free of charge within 1-3 workdays
- 100 days right of return
- Live-long first aid in case of technical questions
- On-site repair service available



Questions? Contact our product experts.

 \oslash 0800 - 000 96 25

