

Electric stacker **EXACT**





Why the EXACT?

The Pallit EXACT high lift pallet truck makes logistical challenges easier and increases productivity in your company. Thanks to its proportional lift, it can be raised and lowered with precision, making it perfect for the precise and careful storage of pallets weighing up to 1500 kg in high racks. The model is designed for use in confined spaces and impresses with its high maneuverability.

- **Three options** to choose from: Lifting height 2.5m, 3.0m or 3.5m available
- Powerful AGM battery with 71 Ah capacity
- Flexible battery charging thanks to integrated charger

- High-quality display for permanent monitoring of the battery's energy level and additional information
- Small turning radius of 1490 mm for easy maneuvering in tight spaces
- Powerful and economical thanks to three-phase traction motor
- Improved visibility for operators thanks to Plexiglas screen
- All functions via lever on the handle



Technical data


Electric stacker EXACT

OPTIONS Choose between

Option	0 2 3
Lifting height (h3)	2500 3000 3500 mm
Max. Total height (h4)	2935 3435 3935 mm
Min. total height (h1)	1730 1980 2230 mm

DIMENSIONS

Fork length	1150 mm	- 1
Width	820 mm	b1
Length	1710 mm	I1
Fork width outside	560 mm	b5
Ground clearance	30 mm	m2
Drawbar height	1255 mm	h14
Height from floor	90 mm	h13
Fork width single	160 mm	е
Load center	600 mm	С
Turning radius	1490 mm	Wa
Min. aisle width (EPAL1 Euro pallets)	1952 mm	Branch



GENERAL

Brake type	Electromagnetic
Load capacity	1500 kg
Weight	600 kg
Sound pressure level according to EN 12053	70 db(A)

DRIVE

Drive type	Electric
Motor power	0.75 kW
Travel speed, unloaded	4.5 km/h
Climbing ability, unloaded	15 %
Climbing ability, loaded	5 %

BATTERY

Battery type	AGM
Weight of the battery	50 kg
Battery capacity	71 Ah
Operating time	5 hours
Loading time	7 hours
Battery voltage	12 V
level indicator	Yes
Number of batteries	2
Charger	Integrated, inclusive

LIFT

Lifting speed, unloaded	0.13 m/s
Proportional stroke	Yes
Engine power, stroke	2.2 kW

TREATMENT

Tire material	Polyurethane
Castors	Single
Wide castors	70 mm
Diameter of rollers	80 mm
Wide swivel castors	70 mm
Castor diameter	210 mm

We are constantly improving our products. For this reason, technical data may change without prior notice. Details of our manufacturer's warranty "Basic Warranty" can be found in our warranty statement. The pallet truck complies with EU safety regulations.



Pictures

Electric stacker EXACT















Pictures

Electric stacker EXACT









Why Pallit?

- Free delivery in 1-3 working days
- 100-day return policy
- Five-year basic warranty on all pallet trucks
- First aid for technical issues for life
- On-site repair service available



© 0800 - 000 96 25