

PRODUCT FICHE

Supplier's name	VALLOX OY
Product model name	Vallox TSK Multi 50 MV
Cell	Aluminium
SEC cold climate	-79.733 kWh/m ² a
SEC average climate	-40.955 kWh/m ² a
SEC warm climate	-16.113 kWh/m ² a
SEC-class cold climate	A+
SEC-class average climate	A
SEC-class warm climate	E
General topology EcoDesign	Bidirectional
Motor & drive EcoDesign	Variable speed
Type of heat recovery system	Recuperative
Temperature efficiency of heat recovery	86 %
Maximum supply airflow EcoDesign	169 m ³ /h
Input power of fans at maximum airflow (W)	98 W
Sound power level	47 dB (L _{WA})
Reference airflow rate	0.0330 m ³ /s
Reference pressure difference	50 Pa
Specific power input (SPI)	0.3600
Ventilation control EcoDesign	Local demand control
Specified maximum internal leak of the enclosure	2.0 %
Specified maximum external leak of the enclosure	2.0 %
Filter replacement	"Change filter!" text will appear on the control panel screen. Regular filter replacement is very important for the unit's faultless performance and energy efficiency.
Demolition and removal instructions	www.vallox.com
AEC cold climate	772.5 kWh/a
AEC average climate	235.5 kWh/a
AEC warm climate	190.5 kWh/a
AHS cold climate	9031.6 kWh
AHS average climate	4616.8 kWh
AHS warm climate	2087.6 kWh