

Quick Selection Table											
	Volume flow rate, qv (m³/s)										
Static pressure difference (Pa)	50	100	150	200	250	300	400	500	600	700	800
ATEX fan VDD 200/4 Ex	0,133	0,1	0,0025								
ATEX fan VDD 225/4 Ex	0,194	0,166	0,0944								
ATEX fan VDD 250/4 Ex	0,319	0,272	0,205	0,111							
ATEX fan VDD 315/4 Ex	0,727	0,686	0,6333	0,563	0,483	0,363	0,0019				
ATEX fan VDD 355/4 Ex	1,144	1,086	1,008	0,9444	0,85	0,755	0,441	0,063			
ATEX fan VDD 400/4 Ex	1,516	1,461	1,402	1,344	1,272	1,188	0,988	0,661	0,208		
ATEX fan VDD 400/6 Ex	0,916	0,8222	0,688	0,53	0,105						
ATEX fan VDD 450/4 Ex	2,144	2,082	2,011	1,938	1,866	1,775	1,575	1,311	0,961	0,519	0,066
ATEX fan VDD 450/6 Ex	1,336	1,208	1,058	0,83	0,527	0,227					
ATEX fan VDD 500/4 Ex	2,525	2,447	2,361	2,275	2,188	2,105	1,916	1,713	1,48	1,147	0,275
ATEX fan VDD 500/6 Ex	1,48	1,341	1,116	0,98	0,725	0,341					
ATEX fan VDD 560/6 Ex	2,35	2,22	2,077	1,955	1,827	1,652	1,447	0,494			
ATEX fan VDD 630/6 Ex	3,95	3,805	3,65	3,502	3,311	3,094	2,577	1,716	0,741	0,05	