

PRODUCT FICHE

Supplier's name	VALLOX OY
Product model name	MyVallox 119 CFi enthalpy
Cell	Enthalpy
SEC cold climate	-82.049 kWh/m ² a
SEC average climate	-42.934 kWh/m ² a
SEC warm climate	-17.900 kWh/m ² a
SEC-class cold climate	A+
SEC-class average climate	A+
SEC-class warm climate	E
General topology EcoDesign	Bidirectional
Motor & drive EcoDesign	Variable speed
Type of heat recovery system	Recuperative
Temperature efficiency of heat recovery	88 %
Maximum supply airflow EcoDesign	416 m ³ /h
Input power of fans at maximum airflow (W)	157 W
Sound power level	42 dB (L _{WA})
Reference airflow rate	0.0810 m ³ /s
Reference pressure difference	50 Pa
Specific power input (SPI)	0.2370
Ventilation control EcoDesign	Local demand control
Specified maximum internal leak of the enclosure	2.0 %
Specified maximum external leak of the enclosure	2.0 %
Filter replacement	"Change filter!" text will appear on the control panel screen. Regular filter replacement is very important for the unit's faultless performance and energy efficiency.
Demolition and removal instructions	www.vallox.com
AEC cold climate	707.4 kWh/a
AEC average climate	170.4 kWh/a
AEC warm climate	125.4 kWh/a
AHS cold climate	9100.5 kWh
AHS average climate	4652.0 kWh
AHS warm climate	2103.6 kWh