

SNABBVALSTABELL

	Volymflöde, qv (m ³ /s)												
Skillnad i statiskt tryck (Pa)	0	10	20	30	40	50	60	80	100	120	140	160	200
Axial fläkt HWW EC 250 A	0,547	0,539	0,506	0,497	0,486	0,467	0,428	0,369	0,311	0,211			
Axial fläkt HWW EC 315 A	0,772	0,767	0,747	0,725	0,706	0,675	0,656	0,600	0,522	0,433	0,356		
Axial fläkt HWW EC 355 A	0,808	0,794	0,744	0,733	0,717	0,692	0,667	0,606	0,547	0,467			
Axial fläkt HWW EC 355 B	1,153	1,136	1,128	1,122	1,106	1,089	1,072	1,036	0,989	0,936	0,900	0,856	
Axial fläkt HWW EC 400 A	1,331	1,300	1,267	1,261	1,250	1,222	1,197	1,156	1,100	1,044	1,011	0,978	0,900
Axial fläkt HWW EC 400 B	1,569	1,556	1,547	1,539	1,525	1,514	1,497	1,458	1,406	1,350	1,317	1,283	1,194
Axial fläkt HWW EC 450 A	1,828	1,817	1,797	1,778	1,761	1,737	1,722	1,683	1,636	1,583	1,544	1,508	1,436
Axial fläkt HWW EC 450 B	2,094	2,106	2,094	2,053	2,036	2,019	1,967	1,925	1,883	1,856	1,800	1,744	1,536
Axial fläkt HWW EC 500 A	2,386	2,372	2,353	2,333	2,317	2,294	2,264	2,228	2,189	2,150	2,114	2,080	1,920
Axial fläkt HWW EC 500 B	2,675	2,664	2,647	2,622	2,597	2,575	2,542	2,500	2,456	2,414	2,369	2,331	2,236
Axial fläkt HWW EC 560	2,886	2,881	2,859	2,830	2,797	2,761	2,719	2,664	2,603	2,533	2,492	2,442	2,325
Axial fläkt HWW EC 630	3,767	3,753	3,733	3,699	3,667	3,630	3,594	3,547	3,483	3,411	3,350	3,294	3,128
Axial fläkt HWW EC 710	5,389	5,256	5,114	5,058	4,992	4,858	4,789	4,620	4,325	3,939	3,769	3,655	3,128