

ONLINE CONTROL

The free **MyVallox Cloud** service enables the user to control the ventilation system anytime and anywhere when the unit is connected to the internet. The software of MyVallox units that have been connected to the cloud service is updated automatically.

The unit can also be connected to the home network, allowing it to be controlled through a terminal device that is connected to the home network via the **MyVallox Home** service.

CARBON DIOXIDE SENSOR

The integrated carbon dioxide sensor boosts ventilation automatically when the carbon dioxide level increases. The air remains fresh, even with many people present in the apartment.

HUMIDITY SENSOR

The integrated humidity sensor boosts ventilation based on the need, e.g. after a sauna or shower. The sensor also reduces ventilation when excess moisture has been removed.

CONTROL PANEL

Wall-mounted control panels suited for MyVallox units: **MyVallox Control** and **MyVallox Touch** equipped with a touch screen.

ADDITIONAL CONNECTIONS

For instance, a separate fireplace switch, an At Home/Away switch, or a cooker hood that enables adjusting the efficiency of ventilation can be connected to the unit.

HOUSE AUTOMATION

MyVallox units can be directly connected to a Modbus. KNX can be used with a bus adapter.

EXTERNAL SENSORS

Optional wall-mountable external sensors can be connected to MyVallox units.

In larger apartments in particular, it may be useful to install room-specific **carbon dioxide or humidity sensors**, so that the automatic boost will work faster and more efficiently.

The **MyVallox VOC sensor** monitors the indoor air quality, observing organic impurities that are emitted, e.g. from people, detergents, cooking, or building and interior decoration materials

MV VENTILATION UNITS

TECHNICAL SPECIFICATIONS

	Vallox 51K MV	Vallox 51 MV	Vallox TSK Multi 50 MV	Vallox TSK Multi 80 MV	Vallox 096 MV	Vallox 99 MV	Vallox 110 MV	Vallox 125A MV	Vallox 125B MV	Vallox 125C MV	Vallox 125D MV	Vallox 125E MV	Vallox 125F MV	Vallox 125G MV	Vallox 125H MV	Vallox 145 MV	Vallox 245 MV	Vallox 245 MV VKL			
All models have energy-saving EC fans																			All models have energy-saving EC fans		
BIM models of Vallox products can be downloaded for free for Revit and AutoCAD, and MagiCAD and Cadmatic are also supported.																			BIM models of Vallox products can be downloaded for free for Revit and AutoCAD, and MagiCAD and Cadmatic are also supported.		
● = Standard accessory ▲ = Accessory																			● = Standard accessory ▲ = Accessory		
Indicative maximum floor area of the apartment ¹⁾	75 m ²	75 m ²	80 m ²	120 m ²	140 m ²	150 m ²	170 m ²	180 m ²	250 m ²	430 m ²	430 m ²	Indicative maximum floor area of the apartment ¹⁾									
● = supply air ● = extract air ● = outdoor air ● = exhaust air	<p>Explanation of the symbols</p>																		● = supply air ● = extract air ● = outdoor air ● = exhaust air		
Dimensions (w x h x d) without a siphon	598 x 802 x 349	598 x 668 x 349	900 x 236 x 547	1026 x 293 x 626	600 x 545 x 428	598 x 442 x 625	638 x 678 x 472	598 x 525 x 601	Dimensions (w x h x d) without a siphon												
Weight	51 kg	45 kg	48 kg	62 kg	47 kg	62 kg	60 kg	66 kg	Weight												
Duct outlets	4 x ø 125 mm	4 x ø 125 mm	8 x ø 100 mm	8 x ø 125 mm	4 x ø 125 mm	4 x ø 125 mm	4 x ø 160 mm	6 x ø 125 mm	8 x ø 125 mm	4 x ø 160 mm	4 x ø 160 mm	4 x ø 125 mm	4 x ø 160 mm	4 x ø 125 mm	4 x ø 160 mm	4 x ø 125 mm	4 x ø 200 mm	4 x ø 250 mm	4 x ø 250 mm	Duct outlets	
Maximum extract air flow ²⁾ (dm ³ /s/100 Pa)	51	51	56	96	86	99	111	127	127	127	127	127	127	127	127	127	160	271	269	Maximum extract air flow ²⁾ (dm ³ /s/100 Pa)	
Maximum supply air flow ²⁾ (dm ³ /s/100 Pa)	46	46	47	85	81	107	111	111	111	111	111	111	111	111	111	111	142	247	229	Maximum supply air flow ²⁾ (dm ³ /s/100 Pa)	
Specific energy consumption (SEC) in a temperate climate	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A+	A+	A+	Specific energy consumption (SEC) in a temperate climate	
Annual efficiency of heat recovery from extract air*	77 %	77 %	79 %	80 %	77 %	76 %	79 %	75 %	75 %	75 %	75 %	75 %	75 %	75 %	75 %	75 %	79 %	82 %	82 %	Annual efficiency of heat recovery from extract air*	
Specific fan power of the ventilation unit* (kW/m ³ /s)	1,04	1,04	1,30	1,26	1,48	1,12	1,22	1,52	1,52	1,52	1,52	1,52	1,52	1,52	1,52	1,52	1,25	0,68	0,70	Specific fan power of the ventilation unit* (kW/m ³ /s)	
Type of heat exchanger	Cross-counter flow	Type of heat exchanger																			
HR cell bypass	Automatic	Automatic	HR cell bypass																		
Post-heating	Electric resistor	liquid radiator (VKL)	Post-heating																		
Control options																			Control options		
Control methods	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control panel, Cloud service, LAN, Modbus, KNX, 0–10 VDC	Control methods	
Compatible cooker hood for boosting ventilation and controlling the fan speed and ventilation modes	Integrated Vallox Captura cooker hood	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Delico PTD EC, X-Line PTXP MC, X-Line PTXPA MC	Compatible cooker hood for boosting ventilation and controlling the fan speed and ventilation modes	
Compatible cooker hood for boosting ventilation		Delico KTD A, X-Line KTXA	Compatible cooker hood for boosting ventilation																		
Defrosting																			Defrosting		
Defrosting automation	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	Defrosting automation	
HR cell bypass	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	HR cell bypass
Accessories																			Accessories		
Ceiling mounting plate		▲			▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	Ceiling mounting plate
Roof feedthrough					▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	Roof feedthrough
Wall mounting plate	●	●	▲	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	Wall mounting plate
Carbon dioxide sensor	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	Carbon dioxide sensor
Humidity sensor	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	●▲	Humidity sensor
VOC sensor	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	▲	VOC sensor
Fireplace mode	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	Fireplace mode
Cooker fan compensation	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	Cooker fan compensation

¹⁾ The floor areas provided are indicative. The dimensioning must be based on a ventilation plan drawn up by a professional.

²⁾ The actual air flow during operation is around 50–60% of the maximum air flow

*Working point defined in the Ecodesign Directive (2009/125/EC), Southern Finland, Helsinki-Vantaa TRY year 2020.

