



|                       |                  |
|-----------------------|------------------|
| <b>Prod. Ref.</b>     | 78880-N00        |
| <b>Safety cat.</b>    | S3S CI FO SR     |
| <b>Range of sizes</b> | 36 - 48 (3 - 13) |
| <b>Weight (sz. 8)</b> | 595 g            |
| <b>Shape</b>          | A                |
| <b>Width</b>          | 11               |

**Description:** Black water repellent leather shoe, **SANY-DRY**<sup>®</sup> lining, anti-shock, slipping resistant, non metallic **APT PLUS** midsole **Zero Perforation**

**Plus:** High electrical conductivity. Stability of the conductive capability for extended period. **FOOT-PAD ESD** extremely soft and comfortable footbed, **with low electric resistance**. Thanks to the very low density polyurethane, the footbed is self-molding granting a right distribution of the body weight and providing an immediate feeling of comfort. High shock absorption is provided from highly resilient material and a perfect cushion in the central area of the heel. Perfumed sole. **Boa**<sup>®</sup> closure system allows to put on and take off the shoe easily and quickly. Made of aviation INOX steel, Boa<sup>®</sup> laces resist to the highest stress. With one single hand it is possible to set the Boa<sup>®</sup> closure system easily and adjust it to the millimetre (**Micro-adjustability - 1 click = 1 mm**). **TPU toe cap protection**

**Suggested uses:** Footwear for microelectronic industries. Recommendable in **ATEX** environments

**Care and maintenance:** Clean after each use and dry off away from direct heat; treat the leather with a suitable shoe-polish. Avoid contact with aggressive chemicals or extreme temperature. Avoid immersion in sea water, lime water or cement mixed with water

**Recommendation:** It is always necessary to wear socks made of natural fibers i.e. wool or cotton, because they provide the best performance with electrical conductivity. Avoid introducing any foreign body between foot and footbed of the footwear (i.e. insoles or similar items not equipped by the manufacturer), as they could make void the electrical properties the footwear have been conceived for. Do not undervalue the effect of ageing and contamination of the footwear: during time their electrical resistance can be subjected to alterations. It is always important to check the electrical properties of footwear through the use of special testing devices in electrostatic protected area (EPA), according to the European standard CEI EN 61340-5-1

### MATERIALS / ACCESSORIES

### SAFETY TECHNICAL SPECIFICATIONS

|                      |   | Clause<br>EN ISO<br>20345:2022 | Description   | Unit            | Cofra<br>result  | Requirement |            |      |
|----------------------|---|--------------------------------|---|-----------------|--|-------------|------------|------|
| <b>Complete shoe</b> | <b>E.S.D. features</b>  | CEI EN                         |   |                 |  |             |            |      |
|                      |   | 61340-5-1                      | Electric resistance of footwear to floor                      | MΩ              | <b>44,2</b>  | < 1000      |            |      |
|                      |   | 61340-5-1                      | Cross resistance  | MΩ              | <b>74</b>  | ≤ 100       |            |      |
|                      |   | 61340-5-1                      | Charge ability  | V               | <b>80</b>  | < 100       |            |      |
|                      |   | 5.3.2.6                        | Shock resistance (clearance after shock)                      | mm              | <b>15,5</b>  | ≥ 14        |            |      |
|                      |   | 5.3.2.7                        | Compression resistance (clearance after compression)          | mm              | <b>20,5</b>  | ≥ 14        |            |      |
|                      |   | 6.2.1                          | Penetration resistance<br>(PS requirement with Ø 3,0 mm nail) | N               | <b>To 1100 N</b>                                       | ≥ 1100      |            |      |
|                      |   |                                |   |                 | <b>No perforation</b>                                  |             |            |      |
|                      |   |                                | <b>Energy absorption system</b>                               | 6.2.4           | Shock absorption                                       | J           | <b>8,5</b> | ≥ 20 |
|                      |   |                                | <b>Cold insulation</b>  | 6.2.3.2         | Cold insulation (temp. decrease after 30' C at -17 °C) | °C          | <b>35</b>  | □ 10 |
| <b>Upper</b>         | Black water repellent leather<br>thickness 1,8/2,0 mm   | 5.4.6                          | Water vapour permeability                                     | mg/cmq h        | <b>&gt; 4,6</b>  | ≥ 0,8       |            |      |
|                      |   |                                | Permeability coefficient                                      | mg/cmq          | <b>&gt; 38,7</b>                                       | ≥ 15        |            |      |
|                      |   | 6.3                            | Water absorption  |                 | <b>24%</b>   | ≤ 30%       |            |      |
|                      |   |                                | Water penetration   |                 | <b>0,1 g</b>   | ≤ 0,2 g     |            |      |
|                      |   | 5.5.4                          | Water vapour permeability                                     | mg/cmq h        | <b>&gt; 84,7</b>                                       | ≥ 2         |            |      |
| <b>Vamp</b>          | Textile, breathable, abrasion resistant, colour black   | 5.5.4                          | Permeability coefficient                                      | mg/cmq          | <b>&gt; 677,4</b>                                      | ≥ 20        |            |      |
| <b>lining</b>        | Thickness 1,2 mm  | 5.5.4                          | Water vapour permeability                                     | mg/cmq h        | <b>&gt; 64,4</b>                                       | ≥ 2         |            |      |
| <b>Quarter</b>       | <b>SANY-DRY</b> <sup>®</sup> , breathable, abrasion resistant, colour light green and turquoise | 5.5.4                          | Permeability coefficient                                      | mg/cmq          | <b>&gt; 515,4</b>                                      | ≥ 20        |            |      |
| <b>lining</b>        | thickness 1,2 mm  | 5.8.4                          | Abrasion resistance (lost volume)                             | mm <sup>3</sup> | <b>110</b>   | ≤ 150       |            |      |
| <b>Sole</b>          | Polyurethane/TPU with low electrical resistance, directly injected in the upper:                |                                |   |                 |  |             |            |      |

Outsole: lime TPU, slipping resistant, abrasion resistant and hydrocarbons resistant.  
Midsole: black polyurethane, low density, comfortable and anti-shock.

Adherence coefficient of the sole (Slip resistance)

|         |  |      |             |        |
|---------|--|------|-------------|--------|
| 5.8.5   | Flexing resistance (cut increase)                          | mm   | <b>2,4</b>  | ≤ 4    |
| 5.8.7   | Interlayer bond strength                                   | N/mm | <b>3,5</b>  | ≥ 3    |
| 6.4.2   | Hydrocarbons resistance ( $\Delta V$ = volume increase)    | %    | <b>2,3</b>  | ≤ 12   |
| 5.3.5.2 | ceramic + detergent solution – forepart (contact angle 7°) |      | <b>0,61</b> | ≥ 0,36 |
|         | ceramic + detergent solution – heel (contact angle 7°)     |      | <b>0,48</b> | ≥ 0,31 |
| 6.2.10  | SR : ceramic + glycerol – forepart (contact angle 7°)      |      | <b>0,24</b> | ≥ 0,22 |
|         | SR : ceramic + glycerol – heel (contact angle 7°)          |      | <b>0,46</b> | ≥ 0,19 |