



MARCH 2019

**Update on cable compatibility for Broadcast Headsets/ Headphones:
HMD/ HME 26-II series, HD 26 PRO**

SERIES OVERVIEW



HMD 26-II



HMD-26-II-S



HME 26-II

HMD/ HME 26-SERIES: PROFESSIONAL BROADCAST-STANDARD IN EVERY ASPECT!

MODEL	DESCRIPTION	CABLE COMPATIBILITY
<p>HMD 26-II-series</p>  <p>HMD 26-II-100 505771 HMD 26-II-600 505773 HMD 26-II-600S 505775</p>	<p>Closed on-ear Broadcast headset with accurate sound reproduction for Broadcast usage e.g. outdoor broadcast or broadcast van applications, audio transmission in Broadcast quality</p> <ul style="list-style-type: none"> Dynamic, hyper-cardioid microphone for great suppression of surrounding noise Mic frequency response: 40 - 16,000 Hz Headphone frequency response: 20 – 18,000 Hz Variant: HMD 26-II-600 S (single sided headset) Weight w/o a cable: only 200g <p><i>Cable sold separately.</i></p>	<ul style="list-style-type: none"> CABLE-II-X3K1-GOLD #508546 CABLE-II-X4F #505784 CABLE-II-X5 #505785 CABLE-II-6 #508545 CABLE-II-8 #505797 CABLE-H-X3K1 #502456 CABLE-H-X4F #502457 CABLE-H-X5 #502458 CABLE-H-6 #502533



HME 26-II-series



Variants with
Microphone types:

BKE 4-2:

HME 26-II-100,
HME 26-II-600

BKE 4-4:

HME 26-II-600 (4),
HME 26-II-100(4)

Closed on-ear Broadcast headset with pre-polarized condenser mic as an ideal choice when more precise audio reproduction for professional Broadcast applications

- Variants of condenser microphone types available:
 - BKE 4-2 pick-up pattern: omni-directional (40-20,000 Hz)
 - BKE 4-4 pick-up pattern: cardioid (40 -20,000 Hz)
- Immunity against electromagnetic fields (for BKE4-4 variants)
- Headphone frequency response: 20 – 18,000 Hz
- Weight w/o a cable: only 200g

Cable sold separately.

- CABLE-II-X3K1-P48 * #505783
- CABLE-II-X4F #505784
- CABLE-II-X5 #505785
- CABLE-II-6 #508545
- CABLE-II-8 #505797
- CABLE-H-X4F #502457
- CABLE-H-X5 #502458
- CABLE-H-6 #502533

* P48 Power supply necessary because P48 amp is integrated in the connector

HME 26-II-100(4)-P48 505778



Closed on-ear Broadcast headset which is optimized for the use with wireless audio codec devices for interference free operation

- condenser microphone, cardioid (BKE 4-4)
- P48 amplifier is integrated in the earcup
- Immunity against electromagnetic fields (for BKE4-4 variants)

➔ P48 power supply always necessary to power condenser microphone

Cable sold separately.

- CABLE-II-X3K1-GOLD #508546
- CABLE-H-X3K1 #502456
- CABLE-II-6 #508545
- CABLE-II-8 #505797
- CABLE-H-6 #502533

MODEL

DESCRIPTION

CABLE COMPATIBILITY

HD 26 PRO

505691



Closed on-ear Monitoring headphone with linear response (100 ohm) and 1.5m cable with 3.5mm jack + 6.3mm adapter

- dynamic, closed
- Headphone frequency response: 20 – 18,000 Hz
- Sound pressure Level: 105 dB SPL at 1kHz, 1mW, 115 dB SPL at 1kHz, 1 V
- Weight w/o cable: only 180g

- CABLE -M-BK-STEREO-PLUG3.5 SCR #552746