

## Declaration Of Performance

Prefabricated WaterCare Septic Tank 5 PE - 223193130

No.: DoP\_EN\_223193130\_EN12566

Valid from: 2013.06.01

| Identification                                           |                                                                                                                    |
|----------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| 1. Product                                               | Prefabricated WaterCare Septic Tank 5 PE - Gravy (2x Ø110 outputs)                                                 |
| 2. Item number                                           | 223193130                                                                                                          |
| 3. Intended use                                          | Treatment of domestic wastewater                                                                                   |
| 4. Manufacturer                                          | WaterCare ApS<br>Stejlebjergvej 14<br>DK - 5610 Assens<br>Denmark<br>Tel: +45 70 25 65 37<br>Web: www.watercare.dk |
| 5. Authorized representative                             | -                                                                                                                  |
| 6. System of assessment and verification / Notified body | System 3 /<br>Danish Technological Institute                                                                       |
| 7. Harmonized standard / Notified body number            | DS/EN 12566-1:2004<br>Body no. 1320238-1/2007                                                                      |
| 8. Technical Assessment                                  | Not relevant                                                                                                       |



Item number: 223193130

| 9. Declared performance   |                                                                                                                                                                                                                                          |                                    |
|---------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Essential characteristics | Performance                                                                                                                                                                                                                              | Harmonized technical specification |
| Dimensions                | Length: 2300 mm Width: Ø2190 mm<br>Height: 2090 mm (incl. inspection pipe)                                                                                                                                                               | -                                  |
| Weight                    | < 200 kg                                                                                                                                                                                                                                 | -                                  |
| Nominal capacity          | NC2 - 2,315 m³                                                                                                                                                                                                                           | DS/EN 12566-1:2004 Annex A.1       |
| Water tightness           | Passed                                                                                                                                                                                                                                   | DS/EN 12566-1:2004 Annex A.2       |
| Hydraulic efficiency      | 3,83 g of beads                                                                                                                                                                                                                          | DS/EN 12566-1:2004 Annex B         |
| Crushing resistance       | 34,7 kN/m²                                                                                                                                                                                                                               | DS/EN 12566-3:2009 Annex C         |
| Max. installation depth   | 1,5 m (see installation instructions)                                                                                                                                                                                                    | -                                  |
| Material                  | PE                                                                                                                                                                                                                                       | -                                  |
| Reaction to fire          | NPD                                                                                                                                                                                                                                      | -                                  |
| 10. Conformity            | The performance of the product identified in point 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. |                                    |

Signed for and on behalf of the manufacturer by:

Assens, date 06.08.2026

  
WaterCare ApS  
Stejlebjergvej 14  
5610 Assens - Tlf. 70 25 65 37  
E-mail: info@watercare.dk

Martin P. R. Diedrich, Engineer