




Fanuc R2000iC/125L



22.70.021.01 Complete robotic dresspack,
Axis 3-6, without retraction system,
high-flex conduit with ID 64mm



22.70.121.01 Complete robotic dresspack,
Axis 3-6, Tecliner retraction system,
350mm stroke, high-flex conduit with ID 64mm



22.70.321.01 Complete robotic dresspack,
Axis 3-6, TecBox retraction system,
600mm stroke, high-flex conduit with ID 64mm

Product Information

Our robotic dresspacks offer effective cable protection for the most demanding robotic applications. Specifically designed for cable routing on Fanuc R2000iC/125L robots, our dresspacks include mounting brackets, our high-flex EWX-PAE robotic conduit, effective strain relief and optionally, a retraction system for highly dynamic applications.

Conduit Specifications



Mod. Polyamide PA 12



According to IEC EN 61386
Crush Resistance: > 1200 N



According to IEC EN 61386
Cycles: > 5000000 ~



According to IEC EN 61386
Tier: 4



According to IEC EN 61386
System tear-out strength > 100 N



-40...120°F
Short Periods 150°F



acc. to UL94 HB



acc.

Part Number	Axes	Robot Model	Conduit	Retraction System
22.36.021.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE M40/P36	no retraction system
22.36.321.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE M40/P36	TecBox, Size 36, 400mm
22.36.421.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE M40/P36	TecLiner, Size 36, 400mm
22.48.021.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE M50/P48	no retraction system
22.48.321.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE M50/P48	TecBox, Size 48, 400mm
22.48.421.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE M50/P48	TecLiner, Size 48, 400mm
22.70.021.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE 70	no retraction system
22.70.121.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE 70	TecLiner, Size 70, 350mm
22.70.221.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE 70	TecLiner, Size 70, 550mm
22.70.321.01	A3-A6	Fanuc R2000iC/125L	EWX-PAE 70	TecBox, Size 70, 600mm