

Fanuc M710iC/50 and M710iC/70



TL48.02L01 Complete robotic dresspack,
Axis 3-6, without retraction system,
high-flex conduit with Ø 64mm



TL48.32L01 Complete robotic dresspack,
Axis 3-6, Tecliner retraction system,
600mm stroke, high-flex conduit with Ø 64mm



TL48.42L01 Complete robotic dresspack,
Axis 3-6, Teclox retraction system,
600mm stroke, high-flex conduit with Ø 64mm

Product Information

Our robotic dresspacks offer effective cable protection for the most demanding robotic applications. Specifically designed for cable routing on Fanuc M710iC/50 and M710iC/70 robots, our dresspacks include mounting brackets, our high-flex EWS-FNE robotic conduit, effective strain relief and optionally a retraction system for highly dynamic applications.

Conduit Specifications



Mat. Polyamide PA 12



According to IEC EN 61386
Drake Performance > 1200 N



According to IEC EN 61386
Cables > 5000000 N



According to IEC EN 61386
Tier 4



According to IEC EN 61386
System load - not through > 1200 N



48 - 120°



Short Periods 100°



see in 10.94 MB



Part Number	Axis	Robot Model	Conduit	Retraction System
TL36.02L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE B40/P36	no retraction system
TL36.32L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE B40/P36	Teclbox, Size 36, 400mm
TL36.42L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE B40/P36	Tecliner, Size 36, 400mm
TL48.02L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE M50/P48	no retraction system
TL48.32L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE M50/P48	Teclbox, Size 48, 400mm
TL48.42L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE M50/P48	Tecliner, Size 48, 400mm
TL70.02L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE 70	no retraction system
TL70.12L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE 70	Tecliner, Size 70, 350mm
TL70.22L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE 70	Tecliner, Size 70, 550mm
TL70.32L01	A3-A6	Fanuc M710iC/50 and 70	ENX-FNE 70	Teclbox, Size 70, 600mm