



Fanuc R2000iC/125L



22.70.021.01 Complete robotic dresspack,
Axis 3-6, without retraction system,
high-flex conduit with Ø 64mm



22.70.021.01 Complete robotic dresspack,
Axis 3-6, Tecliner retraction system,
600mm stroke, high-flex conduit with Ø 64mm



22.70.021.01 Complete robotic dresspack,
Axis 3-6, Tecliner retraction system,
600mm stroke, high-flex conduit with Ø 64mm

Product Information

Our robotic dresspacks offer effective cable protection for the most demanding robotic applications. Specifically designed for cable routing on Fanuc R2000iC/125L robots, our dresspacks include mounting brackets, our high-flex EMI-PAE robotic conduit, effective strain relief and optionally, a retraction system for highly dynamic applications.

Conduit Specifications



Mat. Polyamide PA 12



According to IEC EN 61386



Double Resistance > 1000 N



According to IEC EN 61386



Cables > 5000000 N

According to IEC EN 61386

Test 4



According to IEC EN 61386

System test - not strength > 1000 N



-40 - 120 °C

Short Period 150 °C



min. 10.500 MPa



UL

Part Number	Axis	Robot Model	Conduit	Retraction System
22.36.021.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 8442/P36	no retraction system
22.36.321.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 8442/P36	Tecliner, Size 36, 400mm
22.36.421.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 8442/P36	Tecliner, Size 36, 480mm
22.48.021.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE M50/P48	no retraction system
22.48.321.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE M50/P48	Tecliner, Size 48, 400mm
22.48.421.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE M50/P48	Tecliner, Size 48, 480mm
22.70.021.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 70	no retraction system
22.70.121.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 70	Tecliner, Size 70, 350mm
22.70.221.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 70	Tecliner, Size 70, 550mm
22.70.321.01	A3-A6	Fanuc R2000iC/125L	EMX-PNE 70	Tecliner, Size 70, 600mm