

Project		Catalog #		Type	
Prepared by		Notes		Date	



Metalux

SkyRidge 24SR LED

2' x 4' Specification Grade Troffer LED Module

Typical Applications

- Commercial Office Spaces • Schools • Hospitals • Retail
- Other Indoor Ambient Applications

Interactive Menu

- Order Information [page 1](#)
- Photometric Data [page 2](#)
- Control Solutions [page 3](#)
- Connected Systems [page 4](#)
- Product Warranty

Product Certification



Product Features




Top Product Features

- Available in 1' x 2', 1' x 4', 2' x 2' and 2' x 4' recessed versions
- Leverages our patented WaveStream Technology with AcuoAim™ optics
- Advanced optical control with optimal illumination
- High performance efficacy up to 146 lumens per watt
- Over 60% energy savings when compared to a fluorescent troffer
- Options to meet Buy American and other domestic preference requirements

Dimensional and Mounting Details



Lamp Configurations



Ceiling Compatibility

Ceiling Type	Notes
Concrete	Yes
Acoustical	Yes
Drop	Yes
Other	See Notes

*See Crystal Frame Kit Accessory in Ordering Information section.

**Where construction is suitable for use in Air-handling and plenum rated spaces in accordance with Section 900.22.02 of the National Electrical Code, Section 4.3.11.3.6.5 of NFPA 70A and Section 900.2.1.6 of NEC.