

Project		Catalog #		Type	
Prepared By		Notes		Date	



HALO Commercial

HC4 | HM4 | 41/41PS

4-inch LED downlight and wall wash

Typical Applications

Office • Healthcare • Hospitality • Institutional • Mixed-Use/Hotel

Interactive Menu

- Order Information [page 3](#)
- Product Specifications [page 4](#)
- Photometric Data [page 5](#)
- Energy & Performance Data [page 6](#)
- Connected Systems [page 10](#)
- Product Warranty

Product Certification



Product Features




Control Compatibility



Top Product Features


- New construction/remodel series; 500 to 6,000 lumens
- Narrow, Medium and Wide distributions; Wall wash with rotatable linear spread lens
- 2700K, 3000K, 3500K, 4000K and 5000K CCT; 80 or 90 CRI
- Universal voltage 120V-277V; Standard 0-10V driver dims to 1%
- Mounting frame converts to remodel that installs from below the ceiling
- Quick Spec emergency backup mounting frames - fast delivery option

Dimensional and Mounting Details



NEW CONSTRUCTION (NEW) REMODEL

Dimension	NEW CONSTRUCTION (NEW)	REMODEL	NEW CONSTRUCTION (NEW)	REMODEL
Beam	5.0"	5.0"	5.0"	5.0"
Medium	5.0"	5.0"	5.0"	5.0"
Wide	5.0"	5.0"	5.0"	5.0"
Depth	5.0"	5.0"	5.0"	5.0"



Additional Product Options