CLEAR CHOICE

BLUE CAPS FOR FLEXIBLE CONDUCTOR

NIMBUS® 4 FLEX

ACCEPTS FINE STRANDED FLEXIBLE CONDUCTOR

EXPANDED CONDUCTOR RANGE UP TO 535.3 DLO

ILSCO®

CLEARCHOICE

NIMBUS® FOR FLEXIBLE CONDUCTOR

Features:

- Accepts flexible conductors
- Patented set screw doesn't require wire sleeve
- Manufactured from high strength 6061-T6 aluminum alloy
- UL Listed and CSA Certified for 600 volts, 90° C
- Cold temperature rated to -45° C
- Plastisol cover is UV resistant
- Removable plugs provide safety and prevent contamination of De-Ox®
- Broad wire range: 750kcmil-14

Benefits:

- Used in industrial, mining, railroad, motor and welding applications
- Reusable
- Dual rated for copper or aluminum conductors
- Ensures reliability
- Application variability
- Long lasting, high dielectric strength
- Prevents oxides from forming
- Reduces inventory requirements

LISTED 453G

LR-29601

TYPE PBTS & PBTD FLEXIBLE NIMBUS® INSULATED MULTI-TAP CONNECTORS: Accepts Flexible Conductor

Single Sided Item ID	Dual Sided Item ID	Number of Ports	Conductor Range			Alternate Conductor Size
PBTS-2-4-F	PBTD-2-4-F	2	8-14 H,I,K,M,DLO			4-14 AWG
PBTS-3-4-F	PBTD-3-4-F	3	8-14 H,I,K,M,DLO			4-14 AWG
PBTS-4-4-F	PBTD-4-4-F	4	8-14 H,I,K,M,DLO			4-14 AWG
PBTS-6-4-F	PBTD-6-4-F	6	8-14 H,I,K,M,DLO			4-14 AWG
PBTS-2-1/0-F	PBTD-2-1/0-F	2	1-14 H,I,K DLO	2-14 M		1/0-14 AWG
PBTS-3-1/0-F	PBTD-3-1/0-F	3	1-14 H,I,K DLO	2-14 M		1/0-14 AWG
PBTS-4-1/0-F	PBTD-4-1/0-F	4	1-14 H,I,K DLO	2-14 M		1/0-14 AWG
PBTS-6-1/0-F	PBTD-6-1/0-F	6	1-14 H,I,K DLO	2-14 M		1/0-14 AWG
PBTS-2-3/0-F	PBTD-2-3/0-F*	2	2/0-6 H,I,K,DLO	1-6 M		3/0-6 AWG
PBTS-3-3/0-F	PBTD-3-3/0-F*	3	2/0-6 H,I,K,DLO	1-6 M		3/0-6 AWG
PBTS-4-3/0-F	PBTD-4-3/0-F*	4	2/0-6 H,I,K,DLO	1-6 M		3/0-6 AWG
PBTS-6-3/0-F	PBTD-6-3/0-F*	6	2/0-6 H,I,K,DLO	1-6 M		3/0-6 AWG
PBTS-2-250-F	PBTD-2-250-F*	2	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG
PBTS-3-250-F	PBTD-3-250-F*	3	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG
PBTS-4-250-F	PBTD-4-250-F*	4	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG
PBTS-6-250-F	PBTD-6-250-F*	6	4/0-6 H,I,K	2/0-6 M	3/0-6 DLO	250kcmil-6 AWG
PBTS-2-350-F	PBTD-2-350-F*	2	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG
PBTS-3-350-F	PBTD-3-350-F*	3	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG
PBTS-4-350-F	PBTD-4-350-F*	4	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG
PBTS-6-350-F	PBTD-6-350-F*	6	250-6 H,I,K	4/0-6 M	262.2-6 DLO	350kcmil-6 AWG
PBTS-2-500-F	PBTD-2-500-F*	2	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG
PBTS-3-500-F	PBTD-3-500-F*	3	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG
PBTS-4-500-F	PBTD-4-500-F*	4	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG
PBTS-6-500-F	PBTD-6-500-F*	6	350-4 H,I,K	4/0-4 M	373.7-4 DLO	600kcmil-4 AWG
PBTS-2-750-F	PBTD-2-750-F*	2	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG
PBTS-3-750-F	PBTD-3-750-F*	3	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG
PBTS-4-750-F	PBTD-4-750-F*	4	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG
PBTS-6-750-F	PBTD-6-750-F*	6	500-3/0 H,I,K	4/0-3/0 M	535.3-3/0 DLO	750kcmil-4/0 AWG

*** Mountable version also available, dual side only. Consult factory for more information.**

ILSCO® CLEARCHOICE® CONNECTORS

ILSCO • 4730 Madison Road, Cincinnati, Ohio 45227, U.S.A.
Phone: (800) 776-9775, (513) 533-6200, Fax: (513) 871-4084 • sales@ilsco.com, www.ilsco.com
ILSCO of Canada Company • 1050 Lakeshore Rd. East, Mississauga, Ontario, L5E 1E4 • Phone: (905) 274-2341, Fax: (905) 274-8763

Printed in U.S.A.

Catalog No. 10/0911
© Copyright 2011 ILSCO Corporation