

Eaton D4PR2A

Catalog Number: D4PR2A

Eaton General-purpose relay, D4 Series, QTY: 1, DPDT contact configuration, 120V coil, 5 A, 240 Vac/30 Vdc resistive load, 2 A, 250 Vac/3A, 30 Vdc inductive full load, 380 Vac/125 Vdc max. operating voltage

General specifications

Product Name	Catalog Number
Eaton General-purpose relay	D4PR2A
UPC	Product Length/Depth
782114160640	1.14 in
Product Height	Product Width
0.5 in	0.51 in
Product Weight	Warranty
0.04 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Compliances	Certifications
RoHS Compliant	cRUus
CE Marked	CSA file No. LR701519
	UL Listed file E65657
	UL Listed file E1491
Catalog Notes	
Indicator lamp available. Consult sales office or customer support center for additional coil voltages.	



Product specifications

Contact configuration

DPDT

Coil voltage

120 V

Series

D4

Inductive full load

2 A at 250 Vac, 3 A at 30 Vdc

Cover

Plain

Quantity

1

Amperage Rating

5A

Voltage - max

380 Vac/125 Vdc

Resistive load

5 A, 240 Vac, 30 Vdc

Resources

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Drawings

[D4_R2 AutoCAD 2D Footprint \(mm\)](#)

[D4_R2 2D Drawing Xchange](#)

[D4_R2 3D Model Xchange](#)

[D4_R2 3D Inventor](#)

[D4_R2 AutoCAD 2D Footprint](#)

[D4_R2 2D PDF](#)

Specifications and datasheets

[Eaton Specification Sheet - D4PR2A](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia