Specifications

Photo is representative

Eaton DH225FRK

Eaton Heavy duty single-throw fused safety switch, Enhanced visible blade, 400 A, NEMA 3R, Two-pole, Two-wire, 240 V, Max Hp: 50, 125, 50 hp (3PH @ Std fuse/time delay/250 Vdc), (2)#1/0-(2)300 kcmil or (1)#1/0-(1)750 kcmil Al

General specifications

PRODUCT NAME	Eaton heavy duty fusible safety switch
CATALOG NUMBER	DH225FRK
UPC	782114001981
PRODUCT LENGTH/DEPTH	7.27 in
PRODUCT HEIGHT	44.74 in
PRODUCT WIDTH	23.08 in
PRODUCT WEIGHT	120 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	NEC 230.62 (C) Compliant Barrier
CERTIFICATIONS	UL Listed
CATALOG NOTES	Suitable for service entrance use with a neutral or ground lug kit installed. Hp ratings apply only when neutral is field installed and switch is used on a grounded B phase system.

Powering Business Worldwide

Physical Attributes

ENCLOSURE	NEMA 3R
ENCLOSURE MATERIAL	Painted galvanized steel
FUSE CLASS PROVISION	Class H
FUSE CONFIGURATION	Fusible without neutral
NUMBER OF POLES	Two-pole
NUMBER OF WIRES	2
TYPE	Heavy duty fusible safety switch

Performance Ratings

AMPERAGE RATING	400A
HP RATING - MAX	50, 125, 50 hp (3PH @ Std fuse/time delay/250 Vdc)
NEMA RATING	NEMA 3R
VOLTAGE RATING	240V

Miscellaneous

PRODUCT CATEGORY	Heavy Duty, Fusible without neutral

Resources

CATALOGS	Commercial Distribution, Switching Devices, Volume 2, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - DH225FRK

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.