

Specifications



Photo is representative



Eaton FAZ-C2/3

Eaton FAZ supplementary protector, UL 1077 Industrial miniature circuit breaker - supplementary protector, Medium levels of inrush current are expected, 2 A, 15 kAIC, Three-pole, 5-10X /n, 50-60 Hz, Standard terminals, C Curve

General specifications

PRODUCT NAME	Eaton FAZ supplementary protector
CATALOG NUMBER	FAZ-C2/3
EAN	4015082788612
PRODUCT LENGTH/DEPTH	2.07 in
PRODUCT HEIGHT	2.07 in
PRODUCT WIDTH	2 in
PRODUCT WEIGHT	0.8 lb
WARRANTY	1 year
CERTIFICATIONS	IEC 60947-2 UL 1077 CSA Std. C22.2 No.235
CATALOG NOTES	Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices.

Physical Attributes

NUMBER OF POLES	Three-pole
TERMINALS	Standard
TYPE	UL 1077 Industrial miniature circuit breaker - supplementary protector

Miscellaneous

APPLICATION	Suitable for applications where medium levels of inrush current are expected
-------------	--

Performance Ratings

AMPERAGE RATING	2 A
CIRCUIT PROTECTION	C curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	15 kAIC
TRIP TYPE	5-10X /n

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-C2/3

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

