Specifications



Photo is representative





Eaton FAZ-C32/3

Eaton FAZ supplementary protector,UL 1077 Industrial miniature circuit breaker - supplementary protector,Medium levels of inrush current are expected,32 A,15 kAIC,Three-pole,5-10X /n,50-60 Hz,Standard terminals,C Curve

General specifications	
PRODUCT NAME	Eaton FAZ supplementary protector
CATALOG NUMBER	FAZ-C32/3
EAN	4015082788766
PRODUCT LENGTH/DEPTH	2.07 in
PRODUCT HEIGHT	2.07 in
PRODUCT WIDTH	2 in
PRODUCT WEIGHT	0.8 lb
WARRANTY	1 year
CERTIFICATIONS	UL 1077 CSA Std. C22.2 No.235 IEC 60947-2
CATALOG NOTES	Positioned for medium inrush startup currents to provide protection for small transformers and pilot devices.

Powering Business Worldwide

Physical Attributes

NUMBER OF POLES	Three-pole
TERMINALS	Standard
TYPE	UL 1077 Industrial miniature circuit breaker - supplementary protector

Performance Ratings

AMPERAGE RATING	32 A
CIRCUIT PROTECTION	C curve
FREQUENCY RATING	50-60 Hz
INTERRUPT RATING	15 kAIC
TRIP TYPE	5-10X /n

Miscellaneous

APPLICATION	Suitable for applications where medium levels of inrush current are expected

Resources

CATALOGS	Circuit Protection, Miniature Circuit Breakers and Supplementary Protectors, Volume 4, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - FAZ-C32/3

PROJECT NAME:	
PROJECT NUMBER:	
PREPARED BY:	
DATE:	

Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

Follow us on social media to get the latest product and support information.

© 2025 Eaton. All Rights Reserved.