

Eaton M22-XW

Catalog Number: M22-XW

Eaton M22 pushbutton plunger bridge, M22 Modular Pushbutton Non-Illuminated Selector Switch Plunger Bridge, 22.5 mm, IP66, NEMA 4X, 13

General specifications



Product Name	Catalog Number
Eaton M22 pushbutton plunger bridge	M22-XW
UPC	Product Height
786685283500	1.58 in
Product Diameter	Product Weight
0.98 in	0.017 lb
Warranty	Compliances
Eaton Selling Policy 25-000, one (1) year CE Marked from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.	Bureau Veritas GoST-R
	Certifications
	CCC Marked CSA Certified Lloyd's Register Certified

Catalog Notes

Plunger needed to actuate center-mounted contact blocks. Used for non-illuminated three-position selector switches only.

Product specifications

Special features

Plunger Bridge

Series

M22

Type

M22

Environmental rating

IP66, NEMA 4X, NEMA 13

Size

22.5 mm

Resources

Brochures

[M22 Pilot Devices](#)

Catalogs

[Eaton's Volume 7—Logic Control, Operator Interface and Connectivity Solutions](#)

Installation instructions

[M22 Operators and Accessories](#)

Specifications and datasheets

[Global Data Sheet - M22-XW](#)

[Eaton Specification Sheet - M22-XW](#)



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



[Eaton.com/socialmedia](https://www.eaton.com/socialmedia)