

Specifications



Photo is representative

Eaton XTCE150G00TD

Eaton XT IEC contactor, 150A, 24-27 Vdc, 0NO-0NC, 150A, Frame G, 90 mm, 10, 25, 30/40, 60, 125, 125 hp (1/3PH @115, 200, 230/200, 230, 460, 575 V), Three-pole, Non-reversing, , Screw terminals, FVNR

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	XTCE150G00TD
EAN	4015082395919
PRODUCT LENGTH/DEPTH	6.2992126 in
PRODUCT HEIGHT	6.69291339 in
PRODUCT WIDTH	4.37007874 in
PRODUCT WEIGHT	0.61729433 lb
COMPLIANCES	RoHS Compliant CE Marked
CERTIFICATIONS	UL Listed CSA Certified IEC 60947 EN 60947
CATALOG NOTES	Screw terminals (6-65A); 5 mm (80-150A); no lugs (185-2000A)
PRODUCT TYPE	Contactors



Powering Business Worldwide

Product specifications

AMPERAGE RATING	150A
HP RATING - MAX	10, 25, 30/ 40, 60, 125, 125 hp (1/3PH @115,200,230/200,230,460,575 V)
NUMBER OF POLES	Three-pole
TYPE	Full voltage non-reversing contactor
TERMINALS	Screw terminals
COIL VOLTAGE	24-27 Vdc
CONTACT CONFIGURATION	0 NO, 0 NC
CONTINUOUS AMPERE RATING	150 A
SERIES	XT IEC
OPERATION	Non-reversing

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTCE150G00TD

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

