

Specifications



Eaton XTMCXFA22

Eaton motor control auxiliary contact, Four-pole, Screw terminals, 2NO-2NC contact configuration, 10A conventional thermal rating, Front mounting, used with XTRM miniature control relays

General specifications

PRODUCT NAME	Eaton motor control auxiliary contact
CATALOG NUMBER	XTMCXFA22
EAN	4015080102885
PRODUCT LENGTH/DEPTH	1.7 in
PRODUCT HEIGHT	1.5 in
PRODUCT WIDTH	1.25 in
PRODUCT WEIGHT	0.09 lb
COMPLIANCES	CE Marked ATEX Compliant CCC Marked
CERTIFICATIONS	IEC 60947 EN 60947 UL Listed CSA Certified
CATALOG NOTES	Screw terminals (6-65A); 5 mm(80-150A); no lugs (185-2000A). Orders must be placed in multiples of package quantity listed.
GLOBAL CATALOG	XTMCXFA22

Product specifications

USED WITH	XTRM miniature control relays
NUMBER OF POLES	Four-pole
TYPE	Miniature Contactor Accessory - Auxiliary Contact
TERMINALS	Screw
CONTACT CONFIGURATION	2 NO-2 NC
MOUNTING METHOD	Front
CONVENTIONAL THERMAL CURRENT	10A
QUANTITY	5

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - XTMCXFA22

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc

Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2025 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

