



Search Parameters:

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

Switches & Disconnects, Disconnect & Safety Switches

Product #: TG4323

Short Description: 100A 3P GD SS N1 240V FUSIBLE SW

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

| | |
|---------------------------|-----------------|
| Category | General Duty |
| Voltage | 240 AC |
| Amperage | 100A |
| Poles | 3 |
| Wires | 4 |
| Fusing | Fusible |
| Enclosure | NEMA 1 (Indoor) |
| Options | None |
| Height | 21.33 in |
| Depth | 4.9 in |
| Width | 9.39 in |
| Weight | 17.0 lb |
| Wire Range (Cu/Al) | 10-1/0 |
| 240 Vac, NEC Std, 1-ph | 7 hp |
| 240 Vac, NEC Std, 3-ph | 15 hp |
| 240 Vac, Time Delay, 1-ph | 15 hp |
| 240 Vac, Time Delay, 3-ph | 30 hp |
| 250 Vdc | 20 hp |
| GSA Compliance | Yes |
| CSA Certified | Yes |
| UL Listed | Yes |
| GO Schedule | 131A |
| List Price | \$366 |



[View Larger](#)

Publications/Resources

[TG4323](#)

Additional Resources for General Duty

[Application and Technical Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-6](#)

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

