

## Catalog No. TH3364J



### Description 200A 3P HD N5/12 600V FUSIBLE

UPC No 783164087109

### Products > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.

## Specifications

### Descriptors

Category	Heavy Duty
GO Schedule	S1

### Specifications

Voltage	600 AC
Amperage	200 A
Poles	3
Wires	3
Fusing	Fusible
Enclosure	NEMA 5, 12 Drip/Dust-tight
Options	None
Wire Range (Cu/Al)	2-250
480 Vac, NEC Std, 1-ph	25.0 hp
480 Vac, NEC Std, 3-ph	50.0 hp
480 Vac, Time Delay, 1-ph	50.0 hp
480 Vac, Time Delay, 3-ph	125.0 hp
600 Vac, NEC Std, 1-ph	30.0 hp
600 Vac, NEC Std, 3-ph	60.0 hp
600 Vac, Time Delay, 1-ph	50.0 hp
600 Vac, Time Delay, 3-ph	150.0 hp
250 Vdc	40.0 hp
GSA Compliance	Yes

## Classifications

CSA Certified	Yes
UL Listed	Yes

## Dimensions

Height	35.1 in
Depth	5.0 in
Width	14.5 in
Weight	49.0 lb

## Publications

Title	Publication No.	Publication Type
<a href="#">200A (incl. -R suffix) - Safety Switches</a> 1 page outline drawing in .pdf format.	10103091-SH120	Drawings-Outline and Dimensional
<b>Additional Documentation:</b> Visit our <a href="#">Publication Library</a> to find technical documentation, time current curves, CSI Specifications and promotional literature.		