

Description: 16 AWG 2/C STR OAS CL2P, CMP, C(ETL)US FT6  
Specifications: UL Standards 13 & 444, NEC Articles 725 & 800, CSA C22.2 No. 214

#### Construction:

Conductor 16 AWG 26/30 Stranded Bare Copper  
Insulation Plenum PVC  
Insulation Thickness 0.007" nom.  
Insulation Colors Blk,Red  
Insulation Diameter 0.072 nom.  
Lay Length 2.75" nom.  
Drain Wire 24 7/32 TC  
Shield 0.001" Thick Aluminum/Mylar

Jacket Plenum PVC  
Color Natural  
Jacket Thickness 0.015" nom.  
Outside Diameter 0.178" nom.  
Legend (Ink Print)

HONEYWELL P/N 3221 2C16 SHIELDED 3038058 (ETL) CL2P OR CMP C(ETL)US FT6  
(RoHS) W/O# XXXXXX-XXXXXX XXXXX FT DEVICE/ZONE A B C D E F 1 2 3 4 5 6 7 8 9

#### Properties

Temperature Rating -20 to 60 °C  
Operating Voltage 300 Volts max.  
Capacitance 66 pf/ft nom.  
Impedance 31 Ohms nom.  
DC Resistance 4.17 Ohms/M' at 20°C  
Flame Rating NFPA 262, CSA C22.2 No. 2556 (FT6)