

Kellems Wire Management, Cord
Connectors, European Style, .45-.71", PG21,
Black

By Hubbell Wiring Device-Kellems
Catalog # [SECP21BA](#)

Kellems Wire Management, Cord Connectors, European Style,
.45-.71", PG21, Black

Features

- Low profile
- Connector body is a one-piece design with machined threads

Application

Straight Male Connector

Performance

Environmental - Flammability - UL 94V-2, Environmental -
Operating Temperatures - -22°F to 225°F (-30°C to 107°C),
Environmental - Protection Class - IP66 Suitability

Specifications

Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	IP66
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	0.45-0.71 in (11.4-17.9 mm)

Dimensions

Hub Size	PG21
----------	------



Display Size	PG21
General	
Color	Black
Series	Low Profile PG
Specifications	• Body - Nylon • Cord Diameter Inches (mm) - .45"-.71" (11.4-17.9) • Gland - Buna N • Hub Size - PG21
UPC	783585018379
Type	Connector
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Low Profile Cord Connectors
Material	Non-Metallic

Logistics

Pallet Quantity	10800
Carton Quantity	50

Operational

Temperature Rating	Minimum -22 Deg F to 225 Deg F (-30 Deg C to 107 Deg C)
--------------------	--

Product Assets

[Catalog \[English\]](#)
[Catalog Page \[English\]](#)