HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Cord Connectors, European Style, .18-.31", PG9, Gray

By Hubbell Wiring Device-Kellems
Catalog # SECP9GA

Kellems Wire Management, Cord Connectors, European Style, .18-.31", PG9, Gray

Features

- Low profile
- Connector body is a one-piece design with machined threads

Application

Straight Male Connector

Performance

Environmental - Flammability - UL 94V-2, Environmental - Operating Temperatures - -22°F to 225°F (-30°C to 107°C), Environmental - Protection Class - IP66 Suitability

Specifications

Standards - RoHS Compliance Status	CM
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	IP66
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	0.18-0.31 in (4.6-7.9 mm)

Dimensions

Hub Size	PG9
Display Size	PG9

General

Color	Gray
Series	Low Profile PG
Specifications	• Body - Nylon • Cord Diameter Inches (mm) - .18"-.31" (4.6-7.9) • Gland - Buna N • Hub Size - PG9
UPC	783585018249
Type	Connector
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Low Profile Cord Connectors
Material	Non-Metallic

Logistics

Pallet Quantity	33500
Carton Quantity	50

Operational

Temperature Rating	Minimum -22 Deg F to 225 Deg F (-30 Deg C to 107 Deg C)

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved