

Kellems Wire Management, Cord
Connectors, Straight Male, .19"-.25", 1/2",
Nylon

By Hubbell Wiring Device-Kellems
Catalog # [SHC1021CR](#)

Kellems Wire Management, Cord Connectors, Straight Male,
.19"-.25", 1/2", Nylon

Features

- Nylon cord connector resists most common industrial corrosives
- Provides effective pullout protection
- Lightweight design

Application

Straight Male- Form 2

Performance

Environmental - Flammability - UL 94-V2, Environmental - Hazardous Locations - Used in hazardous locations per Class I Div. 2, Class II Div. 1 & 2, Class III Div. 1 & 2 in accordance with the NEC, Environmental - Operating Temperatures - -30°F to +225°F (-34°C to +107°C)

Specifications

Standards - RoHS Compliance	CM
Status	
Environmental Conditions	Suitable For Use In Wet Locations When Used With A Listed Nylon Washer Between Box And Fitting.
EU RoHS Indicator	Yes
Nema Rating	NEMA Type 4, 4X, 12 and 13
Industry Standard(s)	UL Listed

Conductor

Number Of Conductors	Single
Conductor Range	0.19-0.25 in (4.7- 6.3 mm)



Dimensions

Hub Size	1/2 "
Display Size	1/2" NPT

General

Color	Gray
Color Code	Red
Series	Standard Duty Series
Specifications	• Cord Diameter Range Inches (mm) - .19"-.25" (4.7-6.3) • Form Size - F2 • Material - Gray Nylon • NPT Hub Size - 1/2 Inch
UPC	783585208039
Type	Straight Male
Material - Mounting Hardware	Locknut or Tapped Opening
Item Type	Cord Connectors
Material	Nylon

Logistics

Pallet Quantity	6750
Carton Quantity	25

Operational

Temperature Rating	Minimum -30 Deg F to 225 Deg F (-34 Deg C to 107 Deg C)
--------------------	---

Product Assets

- [Catalog \[English\]](#)
- [Catalog Page \[English\]](#)
- [Installation Manual \[English\]](#)