KILLARK®

# GRSS-2L - 3/4" Aluminum GRSS Outlet Body, 7 Internal Hub Config with Mounting Lugs

By Killark
Catalog # GRSS-2L

3/4" Aluminum GRSS Outlet Body, 7 Internal Hub Config with Mounting Lugs

## Features

- Internal hubs
- Blank cover included (Cat. No. GRRBC)
- Compact design and multiple hub configurations
- Furnished with internal ground screw
- Cast-in brackets on cover for use with breaker-bar tools
- Finished with 7 internal hubs:Comes with mounting lugs

## Application

Conduit boxes installed in conduit systems within hazardous areas to: protect conductors in threaded rigid conduit, act as pull and splice boxes, interconnect lengths of conduit, change conduit direction, and provide access to conductors for maintenance and future system changes.

## Specifications

| | |
|---|---|
| UL File Number | E10514 |
| CSA File Number | LR11716 |
| Hazardous Rating(s) | • Class I, Divisions 1 & 2, Groups C, D<br>• Class II, Divisions 1 & 2, Groups E, F, G<br>• Class III, Divisions 1 & 2 |
| EU RoHS Indicator | Contact Manufacturer |

## Dimensions

| | |
|---|---|
| Hub Size | 3/4" |
| Gross Weight with Packaging | 2.69 |

## General

| | |
|---|---|
| Color | Gray |
| UPC | 783936073781 |
| Type | Outlet Body With Cover & Mounting Lugs |
| Material | Aluminum, Copper Free (less than 4/10 of 1%) |
| Cover Type | Blank |
| Finish Type | Powder Epoxy Paint |
| Series | GR Outlet Bodies Series |



© 2026 Hubbell Incorporated. All rights reserved