



# XS Series 3-Pole Tumbler Switch Cover With Device - 15A

By Killark  
Catalog # [XS-8C](#)

XS Series - Aluminum 3-Pole Tumbler Switch Cover With Device - 15A



## Features

- Front lever rotary operated switch assemblies.
- Standard provisions for padlocking in either “ON” or “OFF” position.
- The lever is connected to a threaded stainless steel shaft which passes through the cover.

## Application

Used where making, breaking, or changing connections in an electric circuit is required.

## Specifications

|                     |                                                                                                                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| CSA File Number     | LR11712                                                                                                                                                                                                                                          |
| EU RoHS Indicator   | Contact Manufacturer                                                                                                                                                                                                                             |
| UL File Number      | E53360                                                                                                                                                                                                                                           |
| Hazardous Rating(s) | <ul style="list-style-type: none"><li>• Class I, Divisions 1 &amp; 2, Groups C, D</li><li>• Class I, Zones 1 &amp; 2, Groups IIB, IIA</li><li>• Class II, Divisions 1 &amp; 2, Groups E, F, G</li><li>• Class III, Divisions 1 &amp; 2</li></ul> |

## Conductor

|                 |   |
|-----------------|---|
| Number Of Poles | 3 |
|-----------------|---|

## Configuration

|               |     |
|---------------|-----|
| Back Box Type | SWB |
|---------------|-----|

## Current

|                  |          |
|------------------|----------|
| Frequency Rating | 50/60 Hz |
| Amperage Rating  | 15 A     |

## Dimensions

|                             |                           |
|-----------------------------|---------------------------|
| Length                      | 6.25 in                   |
| Depth                       | 4-1/4 in                  |
| Height                      | 4.875 in                  |
| Width                       | 6 in                      |
| Gross Weight with Packaging | 1.3                       |
| Dimensions                  | 6.25 in x 6 in x 4.875 in |

## General

|          |                                              |
|----------|----------------------------------------------|
| Color    | Gray                                         |
| Series   | XS Series                                    |
| UPC      | 783936925325                                 |
| Type     | Aluminum Tumbler Switch Cover                |
| Material | Aluminum, Copper Free (less than 4/10 of 1%) |

## Operational

|                      |       |
|----------------------|-------|
| Actuator             | Lever |
| Action               | 3P    |
| Horsepower - Maximum | 5     |

## Product Assets

[Installation Manual \[French, English\]](#)