

1. STANDARD:
UNIT TYPE: MI
ORIENTATION: VERTICAL, 0U FULL
OUTLET QTY & TYPE: (18)C13/C15, (18)C13/C15/C19/C2
INPUT VOLTAGE: 200-240/346-415VAC
INPUT CURRENT: 30A(24A DERATED)
BREAKER QTY & TYPE: (3) 16AMP, SINGLE-POLE
INPUT PHASE: 3 PHASE WYE, L-L
RATED POWER: 8.6 KVA
INPUT PLUG: NEMA L21-30P 5W
REGULATORY STANDARD: RoHS COMPLIANT
2. ADDITIONAL:
CORD TYPE: 5W 10AWG SJT
3. ACCESSORIES:
PRODUCT SAFETY WARNING SHEET

1. PRIMARY DIMENSIONS ARE IN MILLIMETERS, SECONDARY DIMENSIONS IN[INCHES]
2. FOR FULL PRODUCT FUNCTIONLITY REFER TO THE USER MANUAL.

PART NUMBER	DESCRIPTION	DIM A	COLOR (-XX)	SHIPPING WEIGHT (KG)
E36D28L	EL2P MI PDU, 30AMP, (18)C13/C15, (18)C13/C15/C19/C21, NEMA L21-30P	3000 +254/-127 [118.1 +10/-5]	BLACK (RAL 9005)	13

[illegible]