



4 in. Rigid/IMC Bonding Locknut

By Raco
Catalog # [1256](#)

4 in. Rigid/IMC Bonding Locknut

Features

- All steel construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- UL and CSA Listed
- Available in trade sizes 1/2 in. through 4 in.

General

Catalog Number	1256
Conduit Type	Rigid/IMC
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Locknuts
Item Type	4D
Material	Steel
UPC	050169012567

Dimensions

Dimensions	0.45 in x 5.05 in x 5.39 in
Height	5.39 in
Length	0.45 in
Trade Size	4 in
Weight	0.275 lb
Width	5.05 in



Certifications And Compliance

Buy America(n) Qualified Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	2940

Product Assets

- [3D Models - 1256_MODEL-PDF](#)
- [3D Models - 1256_MODEL-IGES](#)
- [3D Models - 1256_MODEL-STEP](#)
- [Catalogs - RACO / TayMac / Bell Full Catalog](#)
- [Catalogs - Commercial Fittings](#)
- [Certifications - UL COC - E195975- 1](#)
- [Certifications - UL COC-E195975-2](#)
- [Product Logo - Conduit](#)
- [SDS - HCC SDS](#)
- [Specifications - 1256](#)
- [Terms and Conditions - HCC Terms & Conditions](#)