



2 in. 90 Degree Liquidtight Connector, Uninsulated

By Raco
Catalog # [3428](#)



2 in. 90 Degree Liquidtight Connector, Uninsulated

*Representative Image

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

EU RoHS Indicator	Yes
Material	Steel/Malleable Iron
UPC	050169034286

Dimensions

Dimensions	3.5 in x 3.5 in x 5.875 in
Height	5.875 in
Length	3.5 in
Trade Size	2 in
Weight	2.26 lb
Width	3.5 in

Certifications And Compliance

Certified Listed	• UL Listed • CSA Certified
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	700

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Product Logo - LT COND](#)
[Sales Drawings - 3428](#)
[SDS - HCC_SDS](#)
[Terms and Conditions - HCC Terms & Conditions](#)
[Video - RACO: Liquidtight Connectors vs. popular competitor](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3428-SPEC-EN | REV 6/2024