

Square Boxes and Covers

4" Square Partitions

Applications

- Low voltage partitions may be added to conduit-type boxes to divide power from voice/data
- Must be used with raised covers

Product Features


- Partition divides 4" square boxes into two compartments
- Use with two-device covers which have a slot for the partition
- Partition is scored so it can be broken at the proper depth of box and cover combination
- Helpful hint: Assemble the box with the partition in place before breaking off at the scored tab. This will prevent you from breaking off more tab than needed



706RAC



707RAC



709

Low Voltage Partitions

Cat. #	Description	Std. Pkg.	Bar Code
For 1-1/2" Depth Boxes and 2-Device Covers			
706RAC	Fits 1/4" to 1" Cover Depth (#777, 8777-0, 778, 769, 8769, 8778, 779, 8779, 780)	25	—
For 2-1/8" Depth Boxes and 2-Device Covers*			
707RAC	Fits 1/4" to 1" Cover Depth (#777, 8777-0, 778, 769, 8769, 8778, 779, 8779, 780)	25	—
709	Fits 1-1/4", 1-1/2" or 2" Cover Depth (#781, 8781, 795, 796)	25	—

Notes: Boxes, covers, and partitions must be ordered separately.

For 5/8" cover depth, use the 3/4" break.

Partitions are usable but not UL listed for 4-11/16" sq. box.

4" Square Fixture Covers

Applications

- Raised fixture covers are used where fixtures will be installed

Product Features

- Angled mounting slots compensate up to 12° for box misalignment
- Swivel covers restricted to 20° swing from vertical
- KWIK-HANG® 897KH allows easy installation of high bay lighting fixtures. Fixture rests in position while wiring is completed

756-759, 767,
8756, 8767

897KH

4" Square Covers

Cat. #	Description	Cubic Inches (Cm3)	Recommended Max. Loads		Std. Pkg.	Bar Code
			Ceiling Fan (Dynamic) Lbs.	Fixture (Static) Lbs.		
Fixture Covers						
767	Raised, 1/2" Open, Ears 2-3/4" O.C.	3.0 (49.2)	No	50	25	—
8767	Raised, 1/2" Open, Ears 2-3/4" O.C.	3.0 (49.2)	No	50	25	
756	Raised, 5/8" Open, Ears 2-3/4" O.C.	4.0 (65.5)	No	50	100	—
8756	Raised, 5/8" Open, Ears 2-3/4" O.C.	4.0 (65.5)	No	50	25	
759	Raised, 3/4" Open, Ears 2-3/4" O.C.	5.0 (81.9)	No	50	25	
757	Raised, 1" Open, Ears 2-3/4" O.C.	6.8 (111.4)	No	50	25	
758	Raised, 1-1/4" Open, Ears 2-3/4" O.C.	8.5 (139.3)	No	50	25	—

Compliance

- UL US LISTED