

SINGLE DEVICE HANDY BOXES & EXTENSION RINGS

6 in. x 2 in. Handy Box Extension Rings, 1-1/2 in. Deep - Welded with Conduit KD's

RAE



Catalog # 100


APPLICATIONS

RACO Handy boxes, also called utility boxes, are used for convenience outlets, switch boxes or small junction boxes.

SALES

File #100075

COMPLIANCE

All RACO single gang, two gang, four gang, and single gang-pangable 20 listed steel boxes are acceptable for use in 2 hour fire rated walls. For additional information, consult UL "Type Resistance (Listing)" at the UL website at www.ul.com

FOR REFERENCE

Acceptable for use in 2 hour rated walls

GENERAL PRODUCT INFORMATION

Wiring System Conduit

CONFIGURATION

End Knockouts 22-1/2 in.
Knockout Type No Knockout
Knockout Number Number
Side Knockouts (N) 1/2 in.
Bottom Knockouts --

DRILLING DIMENSIONS

Dimension A 1-1/2 in.

PRODUCT MEASUREMENTS

Depth 1-1/2 in.
Cuts-inches (mm) 17-1/2 (444.5)
Ht. (in.) (mm) 6.625
Product Length (in.) 1.56
Product Width (in.) 4.50
Product Height (in.) 2.13

PACKAGING

Minimum Pack Qty 25
Box Qty 25
Product UPT # 1 Listed
Weight (lbs.) (Kg.) 40-45
Box Content Length (in.) 17-5/8
Box Content Width (in.) 5.25
Box Content Height (in.) 9.45
Cart Height (in.) 10-1/2
Pallet Qty 2500
UPC Number 000000000000
Unit 000000000000